## **Acetal Co-Polymer Blue FG Sheet Extruded**

Safety Sheet



**Blue Food Grade** 

1.	Substance/preparation	Extruded Acetal-Copolymer Blue Food Grade
2.	Composition / Indications to	Chemical characterization : Polyoxymethylene-Copolymer (POM-C)
	components	<b>Hazardous substances :</b> Product contains no hazardous ingredients liable to be disclosed
3.	Possible dangers	Classification: Not classified
		Physical/ chemical hazards : Flammable
		Health risks: Dust can cause irritation.
		Hazards for the environment: Based on our information, there is no danger to the
		environment.
		The product is according to Directive 1999/45/EC and its annexes are not classified
		as dangerous.
4.	First-aid measures	<b>General information:</b> The product is being classified as non toxic.
		In case of inhalation: If the plastic burns and combustion gases are inhaled, remove
		the person to fresh air and keep warm and seek medical help if necessary.
		In case of skin contact: Burns caused by molten material on skin need to be rapidly
		cooled down with water; do not attempt removal of plastic without medical
		assistance. If irritation develops, seek medical attention.
		In case of eye contact: Flush eyes well with copious quantities of water. Seek
		medical attention, if irritation persists.
		In case of ingestion: The product is non toxic; no first aid procedures are required.
5.	Fire-fighting measures	Suitable extinguisher: Water, foam, gaseous and dry extinguishing media
		Particular endangerments: Hazardous combustion products may emerge.
		Fire fighting and hazardous Water (H2O); carbon dioxide (CO2) and mainly carbon monoxide
		Combustion products (CO): Depending on the amount of available environmental
		oxygen, containing ketones and aldehyde. Formation of further decomposition and
		oxidation products depends upon the fire conditions. Under special fire conditions
		traces of other toxic substances are possible.
		Fire fighting: Approved pressure demand breathing apparatus and protective
		clothing should be used for all fires.
		<b>Additional Information:</b> Residues after the fire, after appropriate rules dispose.
6.	Measures in case of	Personal precautions : N/A
	unintended release	Environmental precaution : N/A
		Methods for cleaning up : Mechanical removal

## **Acetal Co-Polymer Blue FG Sheet Extruded**

**Blue Food Grade** 

Safety Sheet



7.	Handling and storage	<b>Advice on safe handling:</b> During machining of the stock shapes, evacuate swarf to prevent slipping or tripping.
		Storage: Store product in a dry and cool area away from direct sunlight. Keep
		storage and working areas sufficiently ventilated. Keep away form source of flame,
		heat and ignition.
		Due to the risk of collapsing, do not stack more than 2 pallets on top of each other.
		Pallets should not stack on top of each other along aisles.
8.	Limitation of exposition	Ingredients with: CAS-Nr. 50-00-0 (Formaldehyde)
		Occupational exposure Occupational exposure limit (TRGS 900) 0,5 ml/m3 0,62 mg/m3
		Limits to be monitored High limit / Exceedance factor = 1
		Limit values can be fractionally under run by adequate ventilation
		The MAK-Wert for Formaldehyde (TRGS 900) was abrogated with the amendment
		in January 2006. This information only serves as a benchmark.
		General protection: Keep the workplace sufficiently ventilated
		Hygiene measures: Eating and drinking are not allowed.
		Continuous supply of fresh air to the workplace together with removal of processing
		fumes through exhaust systems is recommended. Avoid breathing in gaseous
		degradation products and dust that may result by material overheating.
		Hand protection: Safety gloves in case of contact with warm material
		Eye protection: Safety goggles or shield during machining
		Body protection: Working clothes
		Respiratory protection: Adequate ventilation at workplace is required
9.	Physical and chemical	Aggregate: solid
	characteristics	Colour: product-specific
		Odour: slight, product specific
		Boiling point: N/A
		Melting point: 160 – 175 °C (DIN/EN/ISO 3146)
		Corrosion temperature: N/A
		Flash point: N/A
		Self ignition temperature: 320 – 340 °C (ASTM D1929)
		Explosion hazard or limit: Non explosive
		Oxidizing characteristics: None
		<b>Density:</b> (20 °C): 1.41 g/cm <sup>3</sup> (ISO 1183)
		<b>Solubility:</b> (in Water 20 °C) : insoluble
		Viscosity: N/A
		Additional Information: None

## **Acetal Co-Polymer Blue FG Sheet Extruded**

**Blue Food Grade** 

Safety Sheet



10.	Stability and reactivity	Conditions to avoid: Temperatures above melting point
		Material to avoid: Strong oxidant
		Hazardous decomposition: Formaldehyde CAS-Nr. 50-00-0
		Products: Carbon monoxide CAS-Nr. 630-08-0
		Do not machine together with PVC or other polymers which contain halogenated
		flame retardants.
11.	Toxic information	Toxicology: Based on our experience and information available, no adverse health
		effects are expected if handled as recommended with suitable precautions for
		designated uses.
		Primary Irritation on skin: N/A
		Primary Irritation on eyes: N/A
		Sensitization: Not known
		Practical Tests: N/A
		Additional information: N/A
12.	Ecological information	The material does not harm the environment but is not biologically degradable.
13.	Waste-disposal information	The product must be disposed in accordance with the local authorities.
14.	Transport information	Not classified as hazardous under transport regulations.
15.	Regulation	The product does not require a hazard warning label in accordance with EC directives.
16.	Further information	The information is based on our current knowledge. They are meant to describe our
		products in respect to safety requirements. They do not represent any guarantee of the described product in the sense of the legal guarantee regulations.